




Mocha 1

Recessed Downlight

Order code	KC-030832B01
Input	230VAC
Power rating	10 W
Beam angle	15° / 23° / 36°
Brightness	800 lm
Efficacy	≥80 lm/W
Colour render index(CRI)	≥90
Colour temperature	2700K / 3000K / 4000K / 5000K
UGR	<19
IP level	IP20
Temperature range	-25°C~50°C
Dimming control	Dimmable Optional
Tilttable	Adjustable 30°
Mounting	Recessed
Driver	Driver Included
Warranty	5 years warranty
Lifetime	50,000hrs
Material	Aluminum
Finish	○ White ● Black

(mm)

89



102



102



85*85mm



UGR<19



Voltage



IP level



Adjustable

Finish colour	Beam angle	Colour temperature	Order code
 ☐ White	15°	2700K	KC-030832B01-15D-2700K-W
		3000K	KC-030832B01-15D-3000KW
		4000K	KC-030832B01-15D-4000K-W
		5000K	KC-030832B01-15D-2700K-W
	23°	2700K	KC-030832B01-23D-2700K-W
		3000K	KC-030832B01-23D-3000K-W
		4000K	KC-030832B01-23D-4000K-W
		5000K	KC-030832B01-23D-5000K-W
	36°	2700K	KC-030832B01-36D-2700K-W
		3000K	KC-030832B01-36D-3000K-W
		4000K	KC-030832B01-36D-4000K-W
		5000K	KC-030832B01-36D-5000K-W
 ☒ Black	15°	2700K	KC-030832B01-15D-2700K-B
		3000K	KC-030832B01-15D-3000K-B
		4000K	KC-030832B01-15D-4000K-B
		5000K	KC-030832B01-15D-5000K-B
	23°	2700K	KC-030832B01-23D-2700K-B
		3000K	KC-030832B01-23D-3000K-B
		4000K	KC-030832B01-23D-4000K-B
		5000K	KC-030832B01-23D-5000K-B
	36°	2700K	KC-030832B01-36D-2700K-B
		3000K	KC-030832B01-36D-3000K-B
		4000K	KC-030832B01-36D-4000K-B
		5000K	KC-030832B01-36D-5000K-B