

ATTESTATION OF CONFORMITY

Issued to: Mean Well Enterprises Co., Ltd.
No. 28, Wuquan 3rd Road, Wugu Dist, New Taipei City 248, Taiwan

For the product: LED control gear

Trade name: 

Type/Model: NPF-120y-z (y=D or blank, z=12, 15, 20, 24, 30, 36, 42, 48, 54)

Ratings: Details refer to annex

Manufactured by: Mean Well Enterprises Co., Ltd.
No. 28, Wuquan 3rd Road, Wugu Dist, New Taipei City 248, Taiwan

Requirements: Commission Regulation (EU) No 1194/2012 of 12 December 2012 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for directional Lamps, LED lamps and related equipment.

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a confidential file no. 4320862.50.

This Attestation implies that the examined types are in accordance with the standards designated under the ErP Directive 2009/125/EC.

The examination has been carried out on one single specimen of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of his production with the specimen tested by DEKRA is not the responsibility of DEKRA.

Guangzhou, 18 June 2015

Number: 4320862.01AOC

DEKRA Testing and Certification (Shanghai) Ltd.,
Guangzhou branch



Rosa Zhou
Certification Manager

© Integral publication of this attestation and adjoining reports is allowed

The CE marking may be affixed on the product if all relevant and effective EC directives are complied with



Annex

Document no. : 4320862.01AOC

Independent control gear,

ta: Max. 40 °C, (for NPF-120y-12 and NPF-120y-15)

ta: Max. 45 °C, (for NPF-120y-20, NPF-120y-24, NPF-120y-30, NPF-120y-36, NPF-120y-42, NPF-120y-48, NPF-120y-54)

tc: Max. 90 °C, Class II;

Input:

100-240 Vac, 50/60 Hz, 1,5 A

Output:

12 Vdc, Max. 10 A, 120 W (for NPF-120-12 and NPF-120D-12);

15 Vdc, Max. 8 A, 120 W (for NPF-120-15 and NPF-120D-15);

20 Vdc, Max. 6 A, 120 W (for NPF-120-20 and NPF-120D-20);

24 Vdc, Max. 5 A, 120 W (for NPF-120-24 and NPF-120D-24);

30 Vdc, Max. 4 A, 120 W (for NPF-120-30 and NPF-120D-30);

36 Vdc, Max. 3,4 A, 122,4 W (for NPF-120-36 and NPF-120D-36);

42 Vdc, Max. 2,9 A, 121,8 W (for NPF-120-42 and NPF-120D-42);

48 Vdc, Max. 2,5 A, 120 W (for NPF-120-48 and NPF-120D-48);

54 Vdc, Max. 2,3 A, 124,2 W (for NPF-120-54 and NPF-120D-54)

End