

MODEL : PM-10-5

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1: 80 mVp-p (Max)	I/P: 230VAC O/P:FULL LOAD Ta:25°C	V1: 33 mVp-p (Max)	P
2	OUTPUT VOLTAGE TOLERANCE	V1: 2 %~ -2 % (Max)	I/P:115 VAC / 264 VAC O/P:FULL/ MIN LOAD Ta:25°C	V1: 0.15 %~ -0.15 %	P
3	LINE REGULATION	V1: 1 %~ -1 % (Max)	I/P:115 VAC ~ 264 VAC O/P:FULL LOAD Ta:25°C	V1: 0.12 %~ -0.12 %	P
4	LOAD REGULATION	V1: 1 %~ -1 % (Max)	I/P: 230 VAC O/P:FULL ~MIN LOAD Ta:25°C	V1: 0.12 %~ -0.12 %	P
5	SET UP TIME	230VAC: 1000 ms (Max) 115 VAC: 1000 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 773 ms 115VAC/ 339 ms	P
6	RISE TIME	230VAC: 20 ms (Max) 115VAC: 20 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 4 ms 115VAC/ 5 ms	P
7	HOLD UP TIME	230VAC: 100 ms (TYP) 115VAC: 24 ms (TYP)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 127 ms 115VAC/ 27 ms	P
8	OVER/UNDERSHOOT TEST	< ±5%	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	TEST: <5 %	P
9	DYNAMIC LOAD	V1: 1000 mVp-p	I/P: 230 VAC O/P:FULL /Min LOAD 90%DUTY/1KHZ Ta:25°C	354 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	85VAC~264 VAC	I/P: TESTING O/P: FULL LOAD Ta: 25°C	50 V~264V	P
			I/P: LOW-LINE-3V= 82 V HIGH-LINE+15%=300 V O/P: FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST: OK	
2	INPUT FREQUENCY RANGE	47HZ ~440 HZ NO DAMAGE OSC	I/P: 85 VAC ~ 264 VAC O/P: FULL~MIN LOAD Ta: 25°C	TEST: OK	P
3	EFFICIENCY	74 % (TYP)	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	76.5 %	P
4	INPUT CURRENT	230V/ 0.15 A (TYP) 115V/ 0.25 A (TYP)	I/P: 230 VAC I/P: 115 VAC O/P: FULL LOAD Ta: 25°C	I = 0.12 A/ 230 VAC I = 0.19 A/ 115 VAC	P
5	INRUSH CURRENT	230V/ 45 A (TYP) 115V/ 25 A (TYP) COLD START	I/P: 230 VAC I/P: 115 VAC O/P: FULL LOAD Ta: 25°C	I = 34 A/ 230 VAC I = 18 A/ 115 VAC	P
	LEAKAGE CURRENT	<80uA /264 VAC for touch leakage current	I/P: 264 VAC O/P: Min LOAD Ta: 25°C	L-V+ : 69 uA L-V-: 69 uA N-V+: 69 uA N-V-: 69 uA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	Above 105 %	I/P: 230 VAC I/P: 115 VAC O/P: TESTING Ta: 25°C	147 %/ 230 VAC 142 %/ 115 VAC Hiccup Mode	P
2	OVER VOLTAGE PROTECTION	CH1: 5.75V~ 6.75V	O/P: MIN LOAD Ta: 25°C	6.2V/ 100mA Shut off	P
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 264 VAC O/P: FULL LOAD Ta: 25°C	NO DAMAGE Hiccup Mode	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	No load power consumption	<0.5W	I/P: 240 VAC O/P: NO LOAD0	0.21W/ 240 VAC	P

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																																
1	TEMPERATURE RISE TEST	MODEL : PM-10-5 1. ROOM AMBIENT BURN-IN : 1.5 HRS I/P: 230VAC O/P: FULL LOAD Ta= 27.9℃ 2. HIGH AMBIENT BURN-IN : 1.5 HRS I/P: 230VAC O/P: FULL LOAD Ta= 54℃ <table><tr><th>NO</th><th>Position</th><th>P/N</th><th>ROOM AMBIENT Ta= 22.2 ℃</th><th>HIGH AMBIENT Ta= 51.7 ℃</th></tr><tr><td>1</td><td>U1</td><td>DM0265RNB FAIR</td><td>71.1℃</td><td>92.8℃</td></tr><tr><td>2</td><td>T1 COIL</td><td>TF-1393 LS</td><td>63.0℃</td><td>84.5℃</td></tr><tr><td>3</td><td>C36</td><td>47U/50V RUB 105℃ YXF</td><td>56.5℃</td><td>78.6℃</td></tr><tr><td>4</td><td>D1</td><td>BYV26C 1A/600V VIS</td><td>70.5℃</td><td>92.4℃</td></tr><tr><td>5</td><td>ZD1</td><td>P6KE200A PAN</td><td>71.5℃</td><td>93.3℃</td></tr><tr><td>6</td><td>BD1</td><td>KBP208G 2A/800V LT</td><td>58.5℃</td><td>80.5℃</td></tr><tr><td>7</td><td>D100</td><td>SB1040FCT 10A/40V PEC</td><td>65.4℃</td><td>88.0℃</td></tr><tr><td>8</td><td>C5</td><td>33U/400V NIC 105℃ PT</td><td>55.3℃</td><td>77.9℃</td></tr><tr><td>9</td><td>L100</td><td>DR007D</td><td>55.3℃</td><td>78.1℃</td></tr><tr><td>10</td><td>C105</td><td>470U/16V NCC 105℃ KY</td><td>58.5℃</td><td>81.2℃</td></tr><tr><td>11</td><td>LF1</td><td>LF-501 LS</td><td>55.2℃</td><td>77.3℃</td></tr><tr><td>12</td><td></td><td></td><td></td><td></td></tr><tr><td>13</td><td></td><td></td><td></td><td></td></tr><tr><td>14</td><td></td><td></td><td></td><td></td></tr><tr><td>15</td><td></td><td></td><td></td><td></td></tr></table>			NO	Position	P/N	ROOM AMBIENT Ta= 22.2 ℃	HIGH AMBIENT Ta= 51.7 ℃	1	U1	DM0265RNB FAIR	71.1℃	92.8℃	2	T1 COIL	TF-1393 LS	63.0℃	84.5℃	3	C36	47U/50V RUB 105℃ YXF	56.5℃	78.6℃	4	D1	BYV26C 1A/600V VIS	70.5℃	92.4℃	5	ZD1	P6KE200A PAN	71.5℃	93.3℃	6	BD1	KBP208G 2A/800V LT	58.5℃	80.5℃	7	D100	SB1040FCT 10A/40V PEC	65.4℃	88.0℃	8	C5	33U/400V NIC 105℃ PT	55.3℃	77.9℃	9	L100	DR007D	55.3℃	78.1℃	10	C105	470U/16V NCC 105℃ KY	58.5℃	81.2℃	11	LF1	LF-501 LS	55.2℃	77.3℃	12					13					14					15					P
NO	Position	P/N	ROOM AMBIENT Ta= 22.2 ℃	HIGH AMBIENT Ta= 51.7 ℃																																																																																	
1	U1	DM0265RNB FAIR	71.1℃	92.8℃																																																																																	
2	T1 COIL	TF-1393 LS	63.0℃	84.5℃																																																																																	
3	C36	47U/50V RUB 105℃ YXF	56.5℃	78.6℃																																																																																	
4	D1	BYV26C 1A/600V VIS	70.5℃	92.4℃																																																																																	
5	ZD1	P6KE200A PAN	71.5℃	93.3℃																																																																																	
6	BD1	KBP208G 2A/800V LT	58.5℃	80.5℃																																																																																	
7	D100	SB1040FCT 10A/40V PEC	65.4℃	88.0℃																																																																																	
8	C5	33U/400V NIC 105℃ PT	55.3℃	77.9℃																																																																																	
9	L100	DR007D	55.3℃	78.1℃																																																																																	
10	C105	470U/16V NCC 105℃ KY	58.5℃	81.2℃																																																																																	
11	LF1	LF-501 LS	55.2℃	77.3℃																																																																																	
12																																																																																					
13																																																																																					
14																																																																																					
15																																																																																					
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P: 230 VAC O/P: 125% LOAD Ta:25℃	TEST : OK	P																																																																																
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 230 VAC O/P: 100% LOAD Ta= -20℃	TEST : OK	P																																																																																
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50℃ NO DAMAGE	I/P: 272 VAC O/P:FULL LOAD Ta= 50℃ HUMIDITY= 95 %R.H	TEST : OK	P																																																																																
5	TEMPERATURE COEFFICIENT	± 0.03 %(0~50℃)	I/P: 230 VAC O/P:FULL LOAD	± 0.01 %(0~50℃)	P																																																																																
6	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency:10~500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:2G (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25℃		TEST : OK	P																																																																																

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 4 KVAC/min	I/P-O/P: 4.4 KVAC/min Ta:25°C	I/P-O/P: 0.88 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P: 500 VDC Ta:25°C	I/P-O/P: 30 GΩ NO DAMAGE	P
3	APPROVAL	TUV: Certificate NO : TA 50080232 UL: File NO :			P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	PASS	P
2	CONDUCTION	EN55022 EN55011 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL/50% LOAD Ta:25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 EN55011 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 MEDICAL AIR:8KV / Contact:6KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 MEDICAL INPUT: 2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 MEDICAL L-N :2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

M.T.B.F & LIFE CYCLE CALCULATION

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	CAPACITOR LIFE CYCLE	SUPPOSE C105 IS THE MOST CRITICAL COMPONENT I/P: 230VAC O/P:FULL LOAD Ta= 25 °C LIFE TIME= 229083 HRS I/P: 230VAC O/P:FULL LOAD Ta= 50 °C LIFE TIME= 51263 HRS			P
2	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 723.2KHRS			P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	U1 Rated DM0265RNB : 660 V 1.5A	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2) Full Load (3)Output Short Ta:25℃	(1) 618 V (2) 616 V (3) 616 V	P
2	Diode Peak Voltage	D100 Rated SF10SC4 : 40V 10A	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2) Full Load (3)Output Short Ta:25℃	(1) 28 V (2) 28 V (3) 31 V	P
3	Clamp Diode Peak Voltage	D1 Rated BYV26C : 600V 1 A	I/P:High-Line +3V = 267 V O/P: (1)Full Load (2) Dynamic Load 90%Duty/1KHz Ta:25℃	(1) 572 V (2) 566 V	P
4	Input Capacitor Voltage	C5 Rated :33u / 400V/ 105℃	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change (4)Burn in 1hour Ta:25℃	(1) 388 V (2) 384 V (3) 388 V (4) 388 V	P
5	Control IC Voltage Test	U1 Rated DM0265RNB : 20 V	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta:25℃	(1) 15.4 V (2) 11.2 V (3) 15.4 V	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2005/11/30	RD SAMPLE	PASS	VINCENT TSENG	MAX LIN
2006/4/7	PRODUCT SAMPLE W0601C04	PASS	VINCENT TSENG	MAX LIN

2003/12/12 A50-F023