




Grid 231

Track Lights

Order code	KC-017021A12
Input	48V
Power rating	20W
Beam angle	15° / 36° / 25*45°
Brightness	1700 lm
Efficacy	≥85 lm/W
Colour render index(CRI)	≥90
Colour temperature	2700K / 3000K / 4000K/ 2700K-6000K
UGR	<19
IP level	IP20
Temperature range	-25°C~50°C
Dimming control	Bluetooth APP Control (Default) or DALI (Optional)
Tilttable	Not Adjustable
Mounting	Motion Magnetic Track Series
Driver	48V Driver not Included
Warranty	5 years warranty
Lifetime	50,000hrs
Material	Aluminum
Finish	○ White ● Black

(mm)



Finish colour	Beam angle	Colour temperature	Order code
 ● Black	23°	2700K	KC-017021A12-23D-2700K-B-BLE
		3000K	KC-017021A12-23D-3000K-B-BLE
		4000K	KC-017021A12-23D-4000K-B-BLE
		2700-6000K	KC-017021A12-23D-2700-6000K-B-BLE
	38°	2700K	KC-017021A12-36D-2700K-B-BLE
		3000K	KC-017021A12-36D-3000K-B-BLE
		4000K	KC-017021A12-36D-4000K-B-BLE
		2700-6000K	KC-017021A12-36D-2700-6000K-B-BLE
	25*45°	2700K	KC-017021A12-25.45D-2700K-B-BLE
		3000K	KC-017021A12-25.45D-3000K-B-BLE
		4000K	KC-017021A12-25.45D-4000K-B-BLE
		2700-6000K	KC-017021A12-25.45D-2700-6000K-B-BLE
○ White	23°	2700K	KC-017021A12-23D-2700K-W-BLE
		3000K	KC-017021A12-23D-3000K-W-BLE
		4000K	KC-017021A12-23D-4000K-W-BLE
		2700-6000K	KC-017021A12-23D-2700-6000K-W-BLE
	36°	2700K	KC-017021A12-36D-2700K-W-BLE
		3000K	KC-017021A12-36D-3000K-W-BLE
		4000K	KC-017021A12-36D-4000K-W-BLE
		2700-6000K	KC-017021A12-36D-2700-6000K-W-BLE
	25*45°	2700K	KC-017021A12-25.45D-2700K-W-BLE
		3000K	KC-017021A12-25.45D-3000K-W-BLE
		4000K	KC-017021A12-25.45D-4000K-W-BLE
		2700-6000K	KC-017021A12-25.45D-2700-6000K-W-BLE