




Bend 231C

Track Lights

Order code	KC-017007A12
Input	48V
Power rating	20W
Beam angle	23° / 36° / 60°
Brightness	1980 lm
Efficacy	≥99 lm/W
Colour render index(CRI)	≥90
Colour temperature	2700K / 3000K / 4000K / 2700K-6000K
UGR	<19
IP level	IP20
Temperature range	-25°C~50°C
Dimming control	Bluetooth APP Control (Default) or DALI (Optional)
Tiltable	Adjustable
Mounting	Motion Magnetic Track Series
Driver	48V Driver not Included
Warranty	5 years warranty
Lifetime	50,000hrs
Material	Aluminum
Finish	☐ White ☒ Black

(mm)



Finish colour	Beam angle	Colour temperature	Order code
 ● Black	23°	2700K	KC-017007A12-23D-2700K-B-BLE
		3000K	KC-017007A12-23D-3000K-B-BLE
		4000K	KC-017007A12-23D-4000K-B-BLE
		2700-6000K	KC-017007A12-23D-2700-6000K-B-BLE
	36°	2700K	KC-017007A12-36D-2700K-B-BLE
		3000K	KC-017007A12-36D-3000K-B-BLE
		4000K	KC-017007A12-36D-4000K-B-BLE
		2700-6000K	KC-017007A12-36D-2700-6000K-B-BLE
	60°	2700K	KC-017007A12-60D-2700K-B-BLE
		3000K	KC-017007A12-60D-3000K-B-BLE
		4000K	KC-017007A12-60D-4000K-B-BLE
		2700-6000K	KC-017007A12-60D-2700-6000K-B-BLE
○ White	23°	6000K	KC-017007A12-23D-2700K-W-BLE
		3000K	KC-017007A12-23D-3000K-W-BLE
		4000K	KC-017007A12-23D-4000K-W-BLE
		2700-6000K	KC-017007A12-23D-2700-6000K-W-BLE
	36°	2700K	KC-017007A12-36D-2700K-W-BLE
		3000K	KC-017007A12-36D-3000K-W-BLE
		4000K	KC-017007A12-36D-4000K-W-BLE
		2700-6000K	KC-017007A12-36D-2700-6000K-W-BLE
	60°	2700K	KC-017007A12-60D-2700K-W-BLE
		3000K	KC-017007A12-60D-3000K-W-BLE
		4000K	KC-017007A12-60D-4000K-W-BLE
		2700-6000K	KC-017007A12-60D-2700-6000K-W-BLE