ARCHILIGHT

Product specsheet




Neo 15 Round

Downlight

Order code	FL-FC1024
Input	230 V AC
Power rating	15 W
Beam angle	25° / 40° / 50° / 60°
Brightness	1000 lm
Efficacy	≥67 lm/W
Colour render index(CRI)	≥90
Colour temperature	3000K / 4000K / 5000K / 6000K
UGR	<19
IP level	IP20
Temperature range	-20°C~50°C
Dimming control	Non-Dimmable (Dimmer Optional)
Tiltable	Fixed
Mounting	Surface
Driver	Driver Included
Warranty	5 years warranty
Lifetime	50,000hrs
Material	Aluminum Alloy
Finish	◯White ●Black

(mm)



IP 20

UGR<19 | 220-240V Voltage | IP20 IP level | Fixed

Finish colour	Beam angle	Colour temperature	Order code
 ◯White	25°	2700K	FL-FC1024-2K7-25D-W
		3000K	FL-FC1024-3K-25D-W
		4000K	FL-FC1024-4K-25D-W
		5000K	FL-FC1024-5K-25D-W
	40°	2700K	FL-FC1024-2K7-40D-W
		3000K	FL-FC1024-3K-40D-W
		4000K	FL-FC1024-4K-40D-W
		5000K	FL-FC1024-5K-40D-W
	50°	2700K	FL-FC1024-2K7-50D-W
		3000K	FL-FC1024-3K-50D-W
		4000K	FL-FC1024-4K-50D-W
		5000K	FL-FC1024-5K-50D-W
	60°	2700K	FL-FC1024-2K7-60D-W
		3000K	FL-FC1024-3K-60D-W
		4000K	FL-FC1024-4K-60D-W
		5000K	FL-FC1024-5K-60D-W
 ●Black	25°	2700K	FL-FC1024-2K7-25D-B
		3000K	FL-FC1024-3K-25D-B
		4000K	FL-FC1024-4K-25D-B
		5000K	FL-FC1024-5K-25D-B
	40°	2700K	FL-FC1024-2K7-40D-B
		3000K	FL-FC1024-3K-40D-B
		4000K	FL-FC1024-4K-40D-B
		5000K	FL-FC1024-5K-40D-B
	50°	2700K	FL-FC1024-2K7-50D-B
		3000K	FL-FC1024-3K-50D-B
		4000K	FL-FC1024-4K-50D-B
		5000K	FL-FC1024-5K-50D-B
	60°	2700K	FL-FC1024-2K7-60D-B
		3000K	FL-FC1024-3K-60D-B
		4000K	FL-FC1024-4K-60D-B
		5000K	FL-FC1024-5K-60D-B