





Dot 35 Twin

Track Light

Order code	KC-017001A02
Input	48 V
Power rating	2 * 8W
Beam angle	23° / 36° / 60°
Brightness	456 lm
Efficacy	≥57 lm/W
Colour render index(CRI)	≥90
Colour temperature	2700K / 3000K / 4000K / 2700K - 6000K
UGR	<19
IP level	IP20
Temperature range	-25°C~50°C
Dimming control	Bluetooth APP Control (Default) or DALI (Optional)
Tilttable	Adjustable
Mounting	Motion Magnetic Track Series
Driver	48V Driver not Included
Warranty	5 years warranty
Lifetime	50,000hrs
Material	Aluminum
Finish	☐ White ☒ Black ☒ Black+Gold ☒ White+Gold



Finish colour	Beam angle	Colour temperature	Order code
● Black	23°	2700K	KC-017001A02-23D-2700K-B-BLE
		3000K	KC-017001A02-23D-3000K-B-BLE
		4000K	KC-017001A02-23D-4000K-B-BLE
		2700-6000K	KC-017001A02-23D-2700-6000K-B-BLE
	36°	2700K	KC-017001A02-36D-2700K-B-BLE
		3000K	KC-017001A02-36D-3000K-B-BLE
		4000K	KC-017001A02-36D-4000K-B-BLE
		2700-6000K	KC-017001A02-36D-2700-6000K-B-BLE
	60°	2700K	KC-017001A02-60D-2700K-B-BLE
		3000K	KC-017001A02-60D-3000K-B-BLE
		4000K	KC-017001A02-60D-4000K-B-BLE
		2700-6000K	KC-017001A02-60D-2700-6000K-B-BLE
○ White	23°	2700K	KC-017001A02-23D-2700K-W-BLE
		3000K	KC-017001A02-23D-3000K-W-BLE
		4000K	KC-017001A02-23D-4000K-W-BLE
		2700-6000K	KC-017001A02-23D-2700-6000K-W-BLE
	36°	2700K	KC-017001A02-36D-2700K-W-BLE
		3000K	KC-017001A02-36D-3000K-W-BLE
		4000K	KC-017001A02-36D-4000K-W-BLE
		2700-6000K	KC-017001A02-36D-2700-6000K-W-BLE
	60°	2700K	KC-017001A02-60D-2700K-W-BLE
		3000K	KC-017001A02-60D-3000K-W-BLE
		4000K	KC-017001A02-60D-4000K-W-BLE
		2700-6000K	KC-017001A02-60D-2700-6000K-W-BLE
 ● Black+Gold	23°	2700K	KC-017001A02-23D-2700K-BG-BLE
		3000K	KC-017001A02-23D-3000K-BG-BLE
		4000K	KC-017001A02-23D-4000K-BG-BLE
		2700-6000K	KC-017001A02-23D-2700-6000K-BG-BLE
	36°	2700K	KC-017001A02-36D-2700K-BG-BLE
		3000K	KC-017001A02-36D-3000K-BG-BLE
		4000K	KC-017001A02-36D-4000K-BG-BLE
		2700-6000K	KC-017001A02-36D-2700-6000K-BG-BLE
	60°	2700K	KC-017001A02-60D-2700K-BG-BLE
		3000K	KC-017001A02-60D-3000K-BG-BLE
		4000K	KC-017001A02-60D-4000K-BG-BLE
		2700-6000K	KC-017001A02-60D-2700-6000K-BG-BLE

Finish colour	Beam angle	Colour temperature	Order code
	23°	2700K	KC-017001A02-23D-2700K-WG-BLE
		3000K	KC-017001A02-23D-3000K-WG-BLE
		4000K	KC-017001A02-23D-4000K-WG-BLE
		2700-6000K	KC-017001A02-23D-2700-6000K-WG-BLE
	36°	2700K	KC-017001A02-36D-2700K-WG-BLE
		3000K	KC-017001A02-36D-3000K-WG-BLE
		4000K	KC-017001A02-36D-4000K-WG-BLE
		2700-6000K	KC-017001A02-36D-2700-6000K-WG-BLE
	60°	2700K	KC-017001A02-60D-2700K-WG-BLE
		3000K	KC-017001A02-60D-3000K-WG-BLE
		4000K	KC-017001A02-60D-2700-6000K-WG-BLE
		2700-6000K	KC-017001A02-60D-2700-6000K-WG-BLE