TEST REPORT: MPM-10-3.3

10W Reliable Green Medical Encapsulated Type

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Control Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

DESIGN VERIFY TEST
OUTPUT FUNCTION

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OUTPUT VOLTAGE TOLERANCE (Max)	V1 : 2.5% ~ -2.5%	I/P : 100VAC / 264VAC O/P: FULL / MINLOAD TA= 25℃	V1: 0.54% ~ -0.18%
2	LINE REGULATION (MAX.)	V1 : 0.3% ~ -0.3%	I/P : 100VAC / 264VAC O/P: FULL LOAD TA : 25℃	V1: 0.00% ~ 0.00%
3	LOAD REGULATION(MAX.)	V1 : 0.5% ~ -0.5%	I/P : 230VAC O/P: MIN LOAD ~ FULL LOAD TA : 25℃	V1: 0.18% ~ -0.18%
4	OVER/UNDERSHOOT TEST	< ±15%	I/P : 230VAC O/P: FULL LOAD TA : 25℃	TEST< 4.6 %
5	RIPPLE & NOISE(Max)	V1 : 120 mVp-p	I/P : 230VAC O/P: FULL LOAD TA : 25℃	V1 : 56.8 mVp-p

high frequency:



low frequency:



NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
6	SET UP TIME (MAX.)	230VAC : 1000ms 115VAC : 1000ms	I/P : 230VAC I/P : 115VAC O/P: FULL LOAD TA : 25℃	230VAC : 428ms 115VAC : 384ms

INPUT=230VAC/50HZ @ FULL LOAD

CH1 : Output Voltage CH2 : AC Input Voltage



INPUT=115VAC/60HZ @ FULL LOAD

CH1 : Output Voltage CH2 : AC Input Voltage



7	RISE TIME (MAX.)	230VAC : 30ms 115VAC : 30ms	I/P : 230VAC I/P : 115VAC O/P: FULL LOAD TA : 25℃	230VAC : 7.2ms 115VAC : 7.8ms

INPUT=230VAC/50HZ @ FULL LOAD
CH1 : Output Voltage



INPUT=115VAC/60HZ @ FULL LOAD
CH1 : Output Voltage



8	HOLD UP TIME (TYP.)	230VAC : 40ms 115VAC : 8ms	I/P : 230VAC I/P : 115VAC O/P: FULL LOAD TA : 25℃	230VAC : 70.0ms 115VAC : 14.0ms

INPUT=230VAC/50HZ @ FULL LOAD
CH1 : Output Voltage CH2 : AC Input Voltage



INPUT=115VAC/60HZ @ FULL LOAD
CH1 : Output Voltage CH2 : AC Input Voltage



9	DYNAMIC LOAD	V1 : 990 mVp-p	I/P : 230VAC O/P: (1)Full/Min load 50%duty/120HZ (2)Full/Min load 50%duty/1KHZ TA : 25℃	(1). (2). unit:mVp-p V1: 422mv 356mv

FULL /MIN LOAD 50%DUTY / 120HZ



FULL /MIN% LOAD 50%DUTY / 1KHZ



INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	80VAC ~ 264VAC	I/P : TESTING O/P : FULL LOAD Ta : 25℃	64.0VAC ~ 264VAC
			I/P : LOW-LINE = 97VAC HIGH-LINE = 300VAC O/P : FULL/MIN LOAD ON:30 Sec ; OFF:30 Sec 10MIN (POWER ON/OFF NO DAMAGE)	TEST : OK
2	INPUT FREQUENCY RANGE	47HZ ~ 440HZ NO DAMAGE	I/P : 100VAC ~ 264VAC O/P : FULL~MIN LOAD Ta : 25℃	TEST : OK
3	INPUT CURRENT (TYP.)	0.2A / 230VAC 0.3A / 115VAC	I/P : 230VAC I/P : 115VAC O/P: FULL LOAD TA : 25℃	I= 0.082A / 230VAC I= 0.154A / 115VAC
4	LEAKAGE CURRENT	< 0.08mA	I/P : 240VAC O/P: MIN LOAD TA : 25℃	0.0269 mA
5	NO LOAD POWER CONSUMPTION	< 0.075W	I/P : 230VAC O/P: MIN LOAD TA : 25℃	< 0.0541 W
6	EFFICIENCY (TYP.)	78.0%	I/P : 230VAC O/P: FULL LOAD TA : 25℃	81.3 %



7	INRUSH CURRENT (TYP.)	45A / 230VAC 25A / 115VAC twidth= 555 us measured at 50% Ipeak COLD START	I/P : 230VAC I/P : 115VAC O/P: FULL LOAD TA : 25℃	I= 25.2A / 230VAC I= 11.5A / 115VAC T50= 184.0us / 230VAC

INPUT=230VAC/50HZ @ FULL LOAD

CH2 : AC Input Voltage CH4 : Input current (1V=1A)



INPUT=115VAC/50HZ @ FULL LOAD

CH2 : AC Input Voltage CH4 : Input current (1V=1A)



PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OVER LOAD PROTECTION	110% ~ 180%	I/P: 264VAC I/P: 230VAC I/P: 100VAC O/P: TESTING TA : 25℃	147.60% 264VAC 144.10% 230VAC 131.20% 100VAC Hiccup Mode
2	OVER VOLTAGE PROTECTION	3.80V ~ 5.00V	TA : 25℃	4.40V Shut off o/p voltage,damping by zener diode
3	OVER TEMPERATURE PROTECTION	Shut down Re- power ON	I/P: 264VAC I/P: 80VAC O/P: FULL LOAD	O.T.P. Active Shut down Re- power ON
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 264VAC I/P: 80VAC O/P: FULL LOAD Ta: 25℃	NO DAMAGE Hiccup Mode

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	PWM Power Transistor	U1 Rated： 800V 2.0A	I/P： 267VAC VDS： O/P： (1)Full Load Turn on (2) Output Short (3)Fulll load continue Ta： 25℃	VIN: 267VAC VDS: (1). 512.00V (2). 471.00V (3). 510.00V
2	O/P Diode	D100 Rated： 45V 10.0A	I/P： 267VAC VDS： O/P： (1)Full Load Turn on (2) Output Short (3)Fulll load continue	D100 VDS： (1). 26.30V (2). 30.20V (3). 26.50V
3	Input Capacitor	C5 Rated： 10uf 400V	I/P： 267VAC O/P： (1)Full Load Turn on /Off (2)Min load Turn on /Off (3)Full Load /Min load Change (4)Full Load Continue Ta： 25℃	(1). 376.00V (2). 378.00V (3). 376.00V (4). 376.00V
4	Control IC	U1 Rated： 27V (max) -0.3V (min)	I/P： 267VAC O/P： (1)Full Load (2)Output Short (3)O.L.P (4)Low Line No Load Vo(min) Ta： 25℃	U1 (1). 18.80V (2). 19.20V (3). 20.10V (4). 18.90V
5	Clamp Diode	D2 Rated： 1000V 1.0A	I/P： 267VAC O/P： (1)Dynamic Load Full/Min Load (2)Fulll load continue Ta： 25℃	(1). 484.00V (2). 480.00V

■SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	WITHSTAND VOLTAGE	I/P-O/P： 4.000KVAC /min	I/P-O/P: 4.250KVAC /min Ta： 25℃	I/P-O/P: 0.62mA NO DAMAGE
2	ISOLATION RESISTANCE	I/P-O/P： 500VDC>100MΩ	I/P-O/P: 500VDC Ta： 25℃/70%RH	I/P-O/P: 9999MΩ NO DAMAGE

E.M.C. TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	HARMONIC	EN61000-3-2 CLASS A	I/P： 230VAC /50HZ O/P： FULL LOAD Ta： 25℃	PASS

2	CONDUCTION	EN55011 CLASS B	I/P： 230VAC /50HZ O/P： FULL LOAD / 50% LOAD Ta： 25℃	PASS Test by certified Lab
3	RADIATION	EN55011 CLASS B	I/P： 230VAC /50HZ O/P： FULL LOAD Ta： 25℃	PASS Test by certified Lab
4	E.S.D	EN61000-4-2 MEDICAL AIR：8KV / Contact：8KV	I/P： 230VAC /50HZ O/P： FULL LOAD Ta： 25℃	CRITERIA A
5	E.F.T	EN61000-4-4 MEDICAL INPUT：2KV	I/P： 230VAC /50HZ O/P： FULL LOAD Ta： 25℃	CRITERIA A
6	SURGE	IEC61000-4-5 MEDICAL L-N:1KV;L/N-PE：2KV	I/P： 230VAC /50HZ O/P： FULL LOAD Ta： 25℃	CRITERIA A

RELIABILITY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	TEMPERATURE RISE TEST	MODEL： MPM-10-5 1. ROOM AMBIENT BURN-IN： 1.0hrs IP: 230VAC O/P: 100% LOAD TA= 21.1℃ 2. HIGH AMBIENT BURN-IN： 1.0hrs IP: 230VAC O/P: 100% LOAD TA= 61.0℃		
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P： 230VAC O/P： 132.00% LOAD Ta： 25℃	TEST：OK
3	LOW TEMPERATURE TURN ON TEST	NO DAMAGE 1 HOUR (MIN)	I/P： 264VAC / 100VAC O/P： FULL LOAD Ta： -35.0℃	TEST：OK
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 60℃ NO DAMAGE	I/P： 272VAC O/P： FULL LOAD Ta： 60℃ HUMIDITY= 95.0% RH	TEST：OK
5	TEMPERATURE COEFFICIENT	±0.03% /(0℃~60℃)	I/P： 230VAC O/P： FULL LOAD	±0.0032% /(0℃~60℃)
6	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature： -50℃ ~ +125℃ 2. Temperature change rate ：25℃ / MIN 3. Dwell time low and high temperature ： 30 MIN/EACH 4. Total test cycle：100 CYCLE 5. Input/Output condition： STATIC		TEST：OK
7	THERMAL SHOCK TEST	1. Thermal shock Temperature： -35℃ ~ +65℃ 2. Temperature change rate ：25℃ / MIN 3. Dwell time low and high temperature ： 30 MIN/EACH 4. Total test cycle：16 CYCLE 5. Input/Output condition： 230VAC Full Load AC ON/OFF test turn on 3sec；turn off 1sec @ 15CYCLE 230VAC Full Load AC ON turn on continue @ 1CYCLE		TEST：OK
8	VIBRATION TEST	1 Carton & 1 Set (1) Waveform： Sine Wave (2) Frequency：10~500Hz (4) Acceleration： 5G (5) Test Time： 60 min in each axis (X.Y.Z) (6) Ta：25℃		TEST：OK

NO.	Position	ROOM AMBIENT 21.1℃	HIGH AMBIENT Ta： 61.0℃
1	C4	47.8℃	84.3℃
2	C5	52.3℃	88.3℃
3	C37	47.6℃	83.6℃
4	R1	48.1℃	84.5℃
5	U1	56.9℃	93.5℃
6	T1	57.2℃	92.9℃
7	C101	49.1℃	84.7℃
8	D100	64.3℃	99.8℃
9	BD1	44.1℃	81.7℃
10	D2	61.9℃	98.8℃
60	TA	21.1℃	61.0℃

9	CAPACITOR LIFE CYCLE	:SUPPOSE C101 IS THE MOST CRITICAL COMPONENT								
		(1) I/P：	230VAC	O/P：FULL LOAD	Ta=	25.0℃	LIFE TIME	(1).	429356.8	HRS
		(2) I/P：	230VAC	O/P：FULL LOAD	Ta=	60.0℃	LIFE TIME	(2).	51158.4	HRS
		(3) I/P：	230VAC	O/P：75% LOAD	Ta=	60.0℃	LIFE TIME	(3).	54838.9	HRS
		(4) I/P：	230VAC	O/P：50% LOAD	Ta=	60.0℃	LIFE TIME	(4).	87675.1	HRS
10	MTBF	Conducted by Parts Stress Analysis Prediction 1756.2K hrs min. MIL-HDBK-217F (25℃)								
11	DMTBF /Accelerated Life test	Demonstration Mean Time Between Failure (Expected Life): Above 30000HRS @ TA 60℃								

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	LIUTT		WANGDZ

2007/3/20 A50-S014