

MODEL : RPS-60-5

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1: 60 mVp-p (Max)	I/P: 230VAC O/P:FULL LOAD Ta:25°C	V1: 40 mVp-p (Max)	P
2	OUTPUT VOLTAGE ADJUST RANGE	CH1: 4.75V~ 5.5V	I/P: 230 VAC I/P: 115 VAC O/P:MIN LOAD Ta:25°C	4.63 V~ 5.92 V/ 230 VAC 4.63 V~ 5.92 V/ 115 VAC	P
3	OUTPUT VOLTAGE TOLERANCE	V1: 2 %~ -2 % (Max)	I/P: 115 VAC / 264 VAC O/P:FULL/ MIN LOAD Ta:25°C	V1: 0.3 %~ -0.3 %	P
4	LINE REGULATION	V1: 0.5 %~ -0.5 % (Max)	I/P: 115VAC ~ 264 VAC O/P:FULL LOAD Ta:25°C	V1: 0 %~ 0 %	P
5	LOAD REGULATION	V1: 1%~ -1 % (Max)	I/P: 230 VAC O/P:FULL ~MIN LOAD Ta:25°C	V1: 0.12 %~ -0.12 %	P
6	SET UP TIME	230VAC: 500 ms (Max) 115 VAC: 500 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 383 ms 115VAC/ 368 ms	P
7	RISE TIME	230VAC: 30 ms (Max) 115VAC: 30 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 9 ms 115VAC/ 9 ms	P
8	HOLD UP TIME	230VAC: 50 ms (TYP) 115VAC: 14 ms (TYP)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 80 ms 115VAC/ 15.4 ms	P
9	OVER/UNDERSHOOT TEST	< +5%	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	TEST: <5 %	P
10	DYNAMIC LOAD	V1: 1000 mVp-p	I/P: 230 VAC O/P:FULL /Min LOAD 90%DUTY/1KHZ Ta:25°C	603 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	90VAC~264 VAC	I/P: TESTING O/P: FULL LOAD Ta: 25°C	72 V~264V	P
			I/P: LOW-LINE-3V= 87 V HIGH-LINE+15%=300 V O/P: FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST: OK	
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P: 90VAC ~ 264 VAC O/P: FULL ~MIN LOAD Ta: 25°C	TEST: OK	P
3	EFFICIENCY	79% (TYP)	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	79.2 %	P
4	INPUT CURRENT	230V/ 1 A (TYP) 115V/ 1.8 A (TYP)	I/P: 230 VAC I/P: 115 VAC O/P: FULL LOAD Ta: 25°C	I = 0.62 A/ 230 VAC I = 0.98 A/ 115 VAC	P
5	INRUSH CURRENT	230V/ 60 A (TYP) 115V/ 30 A (TYP) COLD START	I/P: 230 VAC I/P: 115 VAC O/P: FULL LOAD Ta: 25°C	I = 54 A/ 230 VAC I = 27 A/ 115 VAC	P
6	LEAKAGE CURRENT	< 130 uA/ 264 VAC for earth leakage current	I/P: 264 VAC O/P: Min LOAD Ta: 25°C	L-FG: 117 uA N-FG: 117 uA	P
		< 100 uA/ 264 VAC for touch leakage current	I/P: 264 VAC O/P: Min LOAD Ta: 25°C	L-V+ : 79 uA L-V-: 79 uA N-V+: 79 uA N-V-: 79 uA	

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	115 %~ 150 %	I/P: 230 VAC I/P: 115 VAC O/P: TESTING Ta: 25°C	121 %/ 230 VAC 118 %/ 115 VAC Hiccup Mode	P
2	OVER VOLTAGE PROTECTION	CH1: 5.75 V~ 6.75 V	I/P: 230 VAC I/P: 115 VAC O/P: MIN LOAD Ta: 25°C	6.54 V/ 230 VAC 6.54 V/ 115 VAC Shunt down Re- power ON	P
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 264 VAC O/P: FULL LOAD Ta: 25°C	NO DAMAGE Hiccup Mode	P

ONTROL FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	No load power consumption	<0.75W	I/P: 240 VAC O/P: NO LOAD	0.46 W/ 240VAC	P

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																						
1	TEMPERATURE RISE TEST	MODEL : RPS-60-5 1. ROOM AMBIENT BURN-IN : 1 HRS I/P: 230VAC O/P: FULL LOAD Ta= 28.1℃ 2. HIGH AMBIENT BURN-IN : 3 HRS I/P: 230VAC O/P: FULL LOAD Ta= 51.6℃ <table><tr><th>NO</th><th>Position</th><th>P/N</th><th>ROOM AMBIENT Ta= 28.1℃</th><th>HIGH AMBIENT Ta= 51.6℃</th></tr><tr><td>1</td><td>LF1</td><td>LF158</td><td>59.8℃</td><td>78.0℃</td></tr><tr><td>2</td><td>BD1</td><td>US4K 4A/800V SHI</td><td>63.8℃</td><td>81.6℃</td></tr><tr><td>3</td><td>C5</td><td>100U/400V NCC 105℃</td><td>57.4℃</td><td>76.0℃</td></tr><tr><td>4</td><td>D1</td><td>EGP20J 2A/600V ZOW</td><td>89.5℃</td><td>107.7℃</td></tr><tr><td>5</td><td>Q1</td><td>2SK2545 2A/600V TOS</td><td>95.8℃</td><td>112.4℃</td></tr><tr><td>6</td><td>C36</td><td>100U/50V NCC 105℃ KY</td><td>75.7℃</td><td>93.4℃</td></tr><tr><td>7</td><td>T1 COIL</td><td>TF-1414 LS</td><td>82.3℃</td><td>99.8℃</td></tr><tr><td>8</td><td>D100</td><td>SF10SC6 10A/60V SHI</td><td>105.1℃</td><td>120.8℃</td></tr><tr><td>9</td><td>C105</td><td>2200U/10V RUB 105℃ ZLH</td><td>86.2℃</td><td>102.8℃</td></tr><tr><td>10</td><td>L100</td><td>RB023D</td><td>80.1℃</td><td>95.3℃</td></tr><tr><td>11</td><td>U1</td><td>NCP1230D ON</td><td>78.1℃</td><td>96.6℃</td></tr><tr><td>12</td><td>ZD1</td><td>P6KE150A PAN</td><td>78.2℃</td><td>95.3℃</td></tr><tr><td>13</td><td>LF1</td><td>LF158</td><td>59.8℃</td><td>78.0℃</td></tr></table>			NO	Position	P/N	ROOM AMBIENT Ta= 28.1℃	HIGH AMBIENT Ta= 51.6℃	1	LF1	LF158	59.8℃	78.0℃	2	BD1	US4K 4A/800V SHI	63.8℃	81.6℃	3	C5	100U/400V NCC 105℃	57.4℃	76.0℃	4	D1	EGP20J 2A/600V ZOW	89.5℃	107.7℃	5	Q1	2SK2545 2A/600V TOS	95.8℃	112.4℃	6	C36	100U/50V NCC 105℃ KY	75.7℃	93.4℃	7	T1 COIL	TF-1414 LS	82.3℃	99.8℃	8	D100	SF10SC6 10A/60V SHI	105.1℃	120.8℃	9	C105	2200U/10V RUB 105℃ ZLH	86.2℃	102.8℃	10	L100	RB023D	80.1℃	95.3℃	11	U1	NCP1230D ON	78.1℃	96.6℃	12	ZD1	P6KE150A PAN	78.2℃	95.3℃	13	LF1	LF158	59.8℃	78.0℃	P
NO	Position	P/N	ROOM AMBIENT Ta= 28.1℃	HIGH AMBIENT Ta= 51.6℃																																																																							
1	LF1	LF158	59.8℃	78.0℃																																																																							
2	BD1	US4K 4A/800V SHI	63.8℃	81.6℃																																																																							
3	C5	100U/400V NCC 105℃	57.4℃	76.0℃																																																																							
4	D1	EGP20J 2A/600V ZOW	89.5℃	107.7℃																																																																							
5	Q1	2SK2545 2A/600V TOS	95.8℃	112.4℃																																																																							
6	C36	100U/50V NCC 105℃ KY	75.7℃	93.4℃																																																																							
7	T1 COIL	TF-1414 LS	82.3℃	99.8℃																																																																							
8	D100	SF10SC6 10A/60V SHI	105.1℃	120.8℃																																																																							
9	C105	2200U/10V RUB 105℃ ZLH	86.2℃	102.8℃																																																																							
10	L100	RB023D	80.1℃	95.3℃																																																																							
11	U1	NCP1230D ON	78.1℃	96.6℃																																																																							
12	ZD1	P6KE150A PAN	78.2℃	95.3℃																																																																							
13	LF1	LF158	59.8℃	78.0℃																																																																							
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P: 230 VAC O/P: 120 % LOAD Ta:25℃	TEST : OK	P																																																																						
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 230 VAC O/P:100 % LOAD Ta= -20℃	TEST : OK	P																																																																						
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 ℃ NO DAMAGE	I/P: 272 VAC O/P:FULL LOAD Ta= 50℃ HUMIDITY= 95 %R.H	TEST : OK	P																																																																						
5	TEMPERATURE COEFFICIENT	± 0.03 %(0~50℃)	I/P: 230 VAC O/P:FULL LOAD	± 0.01%(0~50℃)	P																																																																						
6	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency:10~500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:2G (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25℃		TEST : OK	P																																																																						

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 4 KVAC/min I/P-FG: 2 KVAC/min O/P-FG: 1.5 KVAC/min	I/P-O/P: 4.2 KVAC/min I/P-FG: 2.4 KVAC/min O/P-FG: 1.8 KVAC/min Ta:25°C	I/P-O/P: 1.95 mA I/P-FG: 1.52 mA O/P-FG: 1.5 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 500 VDC I/P-FG: 500 VDC O/P-FG: 500 VDC Ta:25°C	I/P-O/P: 30 GΩ I/P-FG: 30 GΩ O/P-FG: 30 GΩ NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta:25°C	7 mΩ	P
4	APPROVAL	TUV: Certificate NO : R 50112371 UL: File NO : E227340			P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	PASS	P
2	CONDUCTION	EN55022 EN55011 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL/50% LOAD Ta:25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 EN55011 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 MEDICAL AIR:8KV / Contact:6KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 MEDICAL INPUT: 2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 MEDICAL L-N :1KV L,N-PE:2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

M.T.B.F & LIFE CYCLE CALCULATION

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	CAPACITOR LIFE CYCLE	SUPPOSE C105 IS THE MOST CRITICAL COMPONENT I/P: 230VAC O/P:FULL LOAD Ta= 25°C LIFE TIME= 49521 HRS I/P: 230VAC O/P:FULL LOAD Ta= 50°C LIFE TIME= 14118 HRS I/P: 230VAC O/P: 75% LOAD Ta= 50°C LIFE TIME= 27910 HRS			P
2	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 353.6K HRS			P
3	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure : Above 30,000 hours @ TA 50°C			P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q1 Rated K2545 : 600V 6A	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2) Output Short Ta:25℃	(1) 572 V (2) 590 V	P
2	Diode Peak Voltage	D100 Rated YG805C06 : 60V 20A	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2)Output Short Ta:25℃	(1) 48 V (2) 42 V	P
3	Clamp Diode Peak Voltage	D1 Rated EGP20J : 600V 2A	I/P:High-Line +3V = 267 V O/P: (1) Dynamic Load 90%Duty/1KHz Ta:25℃	(1) 470 V	P
4	Input Capacitor Voltage	C5 Rated :100u / 400V/ 105℃	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta:25℃	(1) 370 V (2) 376 V (3) 370 V	P
5	Control IC Voltage Test	U1 Rated 1230D : 18 V	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta:25℃	(1) 14.1 V (2) 13 V (3) 14 V	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2006/4/3	RD SAMPLE	PASS	VINCENT TSENG	MAX LIN
2006/6/2	PRODUCT SAMPLE W0605A17	PASS	VINCENT TSENG	MAX LIN
2006/7/20	PRODUCT SAMPLE W0607A12	PASS	VINCENT TSENG	MAX LIN

2003/12/12 A50-F023