Bus cables: KNX cable 2x2x0,8mm LSZH Eca 100m green

01890.E

Smart systems&products / KNX / Bus cables / Cable



KNX cable 2x2x0,8mm LSZH Eca 100m green

KNX system cable, 2x2x0,8 mm cable, LSZH sheath, CPR Eca class, according to KNX standard, suitable for installation with I Category power supply cables (U0 = 400 V), green - 100 m reel

Product Status

3 - Active

Minimum order quantity

100 M

Certifications

- **00. CE Marking - EU (download)**
- **27. KNX (download)**

Technical data

Class group: Cables and wires (unassembled)

Class: Data and communication cable

Diameter conductor: 0,80 mm

Nominal cross section conductor: 0,50 mm2

Conductor category: Class 1 = solid

Number of cores: 4

Stranding element: Pairs

Material core insulation: Other

Core identification: Colour

Screen over stranding element: None

Screen over stranding: Foil

Material outer sheath: Other

Colour outer sheath: Green

Outer diameter approximate: 6,00 mm

Permitted cable outer temperature during assembling/handling: 20 - 80 °C

Category: Other

Cable width approximate: 100.000,00 mm

Packaging

8007352574601

Qtà	1 M
Dim	100x0.6x0.6 [cm]
Weight	51.267 [g]

8007352574618

Qtà	100 M
Dim	27x27x11 [cm]
Weight	4,870 [g]

8007352599086

Qtà	300 M
Dim	38x34x24 [cm]
Weight	15,380 [g]

You may also be interested in



01890.C - KNX 2x2x0,8mm LSZH Cca cable-100m green

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.