



Test Report: IRM-60-5

60W Single Output Encapsulated Type

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE(Max)	V1: 80mVp-p	I/P:230VAC O/P:FULL LOAD Ta:25°C	V1: 47.8 mVp-p	P
2	OUTPUT VOLTAGE(Max) TOLERANCE	V1: -2.5%~ 2.5%	I/P: 100VAC /264VAC O/P:FULL/ MIN. LOAD Ta:25°C	V1: -0.618%~ 0.498%	P
3	LINE REGULATION (Max)	V1: -0.5%~ 0.5%	I/P: 100VAC~ 264VAC O/P:FULL LOAD Ta:25°C	V1: -0.12%~ 0%	P
4	LOAD REGULATION(Max)	V1: -1%~ 1%	I/P: 230VAC O/P:FULL ~MIN LOAD Ta:25°C	V1: -0.618%~ 0.498%	P
5	SET UP TIME(Max)	230VAC/1000ms 115VAC/2000ms	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 466.436ms 115VAC/ 570.495ms	P
6	RISE TIME (Max)	230VAC/30ms 115VAC/30ms	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 10.600ms 115VAC/ 11.081ms	P
7	HOLD UP TIME(Typ)	230VAC/50ms 115VAC/12ms	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 92.400ms 115VAC/ 18.221ms	P
8	OVER/UNDERSHOOT TEST	< ±5%	I/P: 230VAC O/P:FULL LOAD Ta:25°C	< ±5%	P
9	DYNAMIC LOAD	V1: 1000mVp-p	I/P: 230VAC O/P(1)FULL /Min LOAD 90%DUTY / 1KHZ (2) (1)FULL /Min LOAD 90%DUTY / 3KHZ (3)FULL /Min LOAD 90%DUTY / 5KHZ (4)FULL /Min LOAD 50%DUTY / 120HZ Ta:25°C	376mVp-p 386mVp-p 378mVp-p 374mVp-p	P
10	TRANSIENT RECOVERY TIME	V1: 1000mVp-p <500us	I/P: 230VAC O/P:40% LOAD CHANGE 50%DUTY/120HZ 1.25A/us	172mVp-p 0 us	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	100VAC~264VAC	I/P:TESTING O/P:FULL LOAD Ta:25°C	71.762V~264V	P
			I/P: (1)LOW-LINE-3V=87 V HIGH-LINE+15%=300 V O/P:FULL/MIN LOAD ON: 30 Sec OFF: 30 Sec 10MIN (2)230Vac ON: 0.5 Sec OFF: 0.5 Sec 20MIN (3)230Vac ON:3Sec OFF:3Sec 12HOURS (POWER ON/OFF NO DAMAGE)	TEST:OK	
2	INPUT FREQUENCY RANGE	47HZ ~440 HZ NO DAMAGE	I/P:100 VAC ~264 VAC O/P:FULL~MIN LOAD Ta:25°C	TEST: OK	P
3	EFFICIENCY(TYP)	84%	I/P:230 VAC O/P:FULL LOAD Ta:25°C	85.24%	P
4	INPUT CURRENT (Typ)	230V/ 1A 115V/ 1.8A	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I =0.483A/ 230VAC I =0.918A/ 115VAC	P
5	INRUSH CURRENT(Typ)	230V/50A 115V/30A COLD START	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I =49.218A/ 230VAC I =28.1A/ 115VAC	P
6	LEAKAGE CURRENT	< 0.25 mA / 240 VAC	I/P : 240 VAC O/P : Min LOAD Ta : 25°C	L-FG : 0.011mA N-FG : 0.011mA	P
7	NO LOAD CONSUMPTION	< 0.1 W	I/P : 115VAC I/P : 230VAC O/P : NO LOAD Ta : 25°C	< 0.0465 W < 0.0625 W	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	115%~ 160%	I/P: 230VAC I/P: 115VAC O/P: TESTING Ta: 25°C	138.24%/ 230VAC 138.04%/115VAC Hiccup Mode	P
2	OVER VOLTAGE PROTECTION	CH: 5.25V~6.75V	I/P: 230VAC I/P: 115VAC O/P: MIN LOAD Ta: 25°C	6.3V shut off o/p voltage, clamping by zener diode	P
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 264VAC O/P: FULL LOAD Ta: 25°C	NO DAMAGE Hiccup Mode	P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	PWM Transistor (D to S) or (C to E) Peak Voltage	Q1 Rated 13A/ 600V	I/P: High-Line +3V = 267V AC ON/OFF VDS: O/P: (1) Full Load (2) Output Short (3) Dynamic Load Full Load/ Min. Load 90%Duty/1KHz (4) Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (5) Dynamic Load Full Load/ Min. Load 90%Duty/5KHz (6) Dynamic Load 100% Load/ Min. Load 50%Duty/120Hz (7) 0%→400% Load. I/P: Low-Line -3V = 97V O/P: (1) Full Load (2) Output Short (3) Dynamic Load Full Load/ Min. Load 90%Duty/1KHz (4) Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (5) Dynamic Load Full Load/ Min. Load 90%Duty/5KHz (6) Dynamic Load 100% Load/ Min. Load 50%Duty/120Hz (7) 0%→400% Load. Ta: 25°C	(1) 566V/A (2) 580V/A (3) 564V/A (4) 560V/A (5) 562V/A (6) 558V/A (7) 588V/A (1) 428V/A (2) 420V/A (3) 418V/A (4) 406V/A (5) 410V/A (6) 422V/A (7) 430V/A	P
2	Diode Peak Voltage	D101 Rated 30A/45V	I/P: High-Line +3V = 267 V AC ON/OFF O/P: (1) Full Load (2) Output Short (3) Dynamic Load Full Load/	Q101: (1) 39.2V (2) 34.6V (3) 40V (4) 40.6V	P

			Min. Load 90%Duty/1KHz (4)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (5)Dynamic Load Full Load/ Min. Load 90%Duty/5KHz (6)Dynamic Load 100% Load/ Min. Load 50%Duty/120Hz (7)0%→400% Load. (8).NO LOAD Ta:25°C	(5)40.6V (6)38.8V (7) 37.6V (8)37.4V	
3	Input Capacitor Voltage	C5 Rated: : 120 μ / 400 V 105°C / VZ Series	I/P:High-Line +3V =267 V O/P: (1)Full Load input on/off (2) Min load input on /Off (3)Full Load /Min load Change Ta:25°C	(1)366V (2)368V (3)366V	P
4	Control IC Voltage Test	PWM IC U1 Rated : 30 V 10 V(MIN.)	I/P:High-Line +3V =267 V AC ON/OFF O/P:(1)FULL LOAD (2) Output Short (3)O.L.P Ta:25°C	(1) 19.8V (2) 17.8V (3) 21.0V	P
5	Clamp Diode Peak Voltage	D 5 Rated : RD 2A/800V	I/P : High-Line +3V = 267 V AC ON/OFF O/P : (1) Dynamic Load 90%Duty/1KHz (2)Full load continue Ta : 25°C	(1) 472 V (2) 472 V	P

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 3KVAC/min	I/P-O/P: 3.6 KVAC/min Ta:25°C	I/P-O/P:1.402mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100M Ω	I/P-O/P: 500 VDC Ta:25°C	I/P-O/P: 9999M Ω NO DAMAGE	P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A	I/P:230VAC/50HZ O/P:100%,75%,50%LOAD Ta:25°C	PASS	P
2	CONDUCTION	EN55022 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL/50% LOAD Ta : 25°C	PASS Test by certified Lab	P
3	E.S.D	EN61000-4-2 INDUSTRY AIR : 8KV / Contact : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
4	E.F.T	EN61000-4-4 INDUSTRY INPUT : 1KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
5	SURGE	IEC61000-4-5 INDUSTRY L-N : 1KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
6	Test by certified Lab & Test Report Prepare				

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																													
1	TEMPERATURE RISE TEST	<div>MODEL : IRM-60-12</div> <div>1. ROOM AMBIENT BURN-IN : 1 HRS</div> <div>I/P : 230VAC O/P : FULL LOAD Ta=32.9℃</div> <div>2. HIGH AMBIENT BURN-IN : 1 HRS</div> <div>I/P : 230VAC O/P : FULL LOAD Ta=50.5℃</div> <table><thead><tr><th>NO</th><th>Position</th><th>ROOM AMBIENT Ta=32.9℃</th><th>HIGH AMBIENT Ta=50.5℃</th></tr></thead><tbody><tr><td>1</td><td>R42</td><td>75.5℃</td><td>94.4℃</td></tr><tr><td>2</td><td>LF1</td><td>69.9℃</td><td>86.7℃</td></tr><tr><td>3</td><td>BD1</td><td>74.4℃</td><td>93.2℃</td></tr><tr><td>4</td><td>C5</td><td>73.6℃</td><td>92.0℃</td></tr><tr><td>5</td><td>D40</td><td>73.2℃</td><td>92.3℃</td></tr><tr><td>6</td><td>U1</td><td>71.1℃</td><td>89.5℃</td></tr><tr><td>7</td><td>D100</td><td>78.0℃</td><td>96.5℃</td></tr><tr><td>8</td><td>LF2</td><td>68.8℃</td><td>86.8℃</td></tr><tr><td>9</td><td>T1</td><td>78.8℃</td><td>98.1℃</td></tr><tr><td>10</td><td>C105</td><td>74.9℃</td><td>90.5℃</td></tr><tr><td>11</td><td>C40</td><td>74.9℃</td><td>93.4℃</td></tr><tr><td>12</td><td>L100</td><td>69.4℃</td><td>88.1℃</td></tr><tr><td>13</td><td>Q1</td><td>78.9℃</td><td>98.7℃</td></tr><tr><td>14</td><td>D5</td><td>78.6℃</td><td>98.5℃</td></tr></tbody></table>			NO	Position	ROOM AMBIENT Ta=32.9℃	HIGH AMBIENT Ta=50.5℃	1	R42	75.5℃	94.4℃	2	LF1	69.9℃	86.7℃	3	BD1	74.4℃	93.2℃	4	C5	73.6℃	92.0℃	5	D40	73.2℃	92.3℃	6	U1	71.1℃	89.5℃	7	D100	78.0℃	96.5℃	8	LF2	68.8℃	86.8℃	9	T1	78.8℃	98.1℃	10	C105	74.9℃	90.5℃	11	C40	74.9℃	93.4℃	12	L100	69.4℃	88.1℃	13	Q1	78.9℃	98.7℃	14	D5	78.6℃	98.5℃		P
NO	Position	ROOM AMBIENT Ta=32.9℃	HIGH AMBIENT Ta=50.5℃																																																															
1	R42	75.5℃	94.4℃																																																															
2	LF1	69.9℃	86.7℃																																																															
3	BD1	74.4℃	93.2℃																																																															
4	C5	73.6℃	92.0℃																																																															
5	D40	73.2℃	92.3℃																																																															
6	U1	71.1℃	89.5℃																																																															
7	D100	78.0℃	96.5℃																																																															
8	LF2	68.8℃	86.8℃																																																															
9	T1	78.8℃	98.1℃																																																															
10	C105	74.9℃	90.5℃																																																															
11	C40	74.9℃	93.4℃																																																															
12	L100	69.4℃	88.1℃																																																															
13	Q1	78.9℃	98.7℃																																																															
14	D5	78.6℃	98.5℃																																																															
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P : 230 VAC O/P : 140% LOAD Ta : 25℃	TEST : OK	P																																																													



60W Single Output Encapsulated Type

IRM-60 series

3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 264VAC/100VAC O/P : 100 % LOAD Ta=30°C	TEST : OK	P
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50°C NO DAMAGE	I/P : 272 VAC O/P : FULL LOAD Ta=50°C HUMIDITY= 95 %R.H	TEST : OK	P
5	TEMPERATURE COEFFICIENT	± 0.03 %/°C (0~50°C)	I/P : 230 VAC O/P : FULL LOAD	± 0.018%/°C (0~50°C)	P
6	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -40°C ~ +80°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK	P
7	THERMAL SHOCK TEST	1. Thermal shock Temperature : -30°C ~ +70°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec		OK	P
8	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 5G (5) Test Time : 60min in each axis (X.Y.Z) (6) Ta : 25°C		TEST : OK	P
9	CAPACITOR LIFE CYCLE	SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta=25°C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta=50 °C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta=50 °C LIFE TIME (4) I/P : 230VAC O/P : 50% LOAD Ta=50 °C LIFE TIME		(1) 139578HRS (2) 28356HRS (3) 55110HRS (4) 95991HRS	P
10	MTBF	MIL-HDBK-217F TOTAL FAILURE RATE : 1226 KHRS			P
11	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure (Expected Life): Above 50,000 hours @ TA 50°C			P

TEST RESULT	TESTER	APPROVAL
PASS	Frank	WANGDZ

2007/3/20 A50-S014