



Slim 150

Downlight

Order code	KC-010197A150
Input	230VAC
Power rating	12W
Beam angle	36° / 60°
Brightness	1044 lm
Efficacy	≥87 lm/W
Colour render index(CRI)	≥90
Colour temperature	2700K / 3000K / 4000K / 5000K
UGR	<19
IP level	IP20
Temperature range	-25°C~50°C
Dimming control	Non-Dimmable or Dimmable
Tiltable	Fixed
Mounting	Surface Mounted
Driver	Driver Included
Warranty	5 years warranty
Lifetime	50,000hrs
Material	Aluminum
Finish	○ White ● Black

(mm)



Non-Dimmable Versions

Finish colour	Beam angle	Colour temperature	Order code
 ○ White	36°	2700K	KC-010197A150-36D-2700K-W
		3000K	KC-010197A150-36D-3000K-W
		4000K	KC-010197A150-36D-4000K-W
		5000K	KC-010197A150-36D-5000K-W
	60°	2700K	KC-010197A150-60D-2700K-W
		3000K	KC-010197A150-60D-3000K-W
		4000K	KC-010197A150-60D-4000K-W
		5000K	KC-010197A150-60D-5000K-W
 ● Black	36°	2700K	KC-010197A150-36D-2700K-B
		3000K	KC-010197A150-36D-3000K-B
		4000K	KC-010197A150-36D-4000K-B
		5000K	KC-010197A150-36D-5000K-B
	60°	2700K	KC-010197A150-60D-2700K-B
		3000K	KC-010197A150-60D-3000K-B
		4000K	KC-010197A150-60D-4000K-B
		5000K	KC-010197A150-60D-5000K-B

Dimmable Versions

 ○ White	36°	2700K	KC-010197A150-36D-2700K-W-TDM
		3000K	KC-010197A150-36D-3000K-W-TDM
		4000K	KC-010197A150-36D-4000K-W-TDM
		5000K	KC-010197A150-36D-5000K-W-TDM
	60°	2700K	KC-010197A150-60D-2700K-W-TDM
		3000K	KC-010197A150-60D-3000K-W-TDM
		4000K	KC-010197A150-60D-4000K-W-TDM
		5000K	KC-010197A150-60D-5000K-W-TDM

Finish colour	Beam angle	Colour temperature	Order code
 Black	36°	2700K	KC-010197A150-36D-2700K-B-TDM
		3000K	KC-010197A150-36D-3000K-B-TDM
		4000K	KC-010197A150-36D-4000K-B-TDM
		5000K	KC-010197A150-36D-5000K-B-TDM
	60°	2700K	KC-010197A150-60D-2700K-B-TDM
		3000K	KC-010197A150-60D-3000K-B-TDM
		4000K	KC-010197A150-60D-4000K-B-TDM
		5000K	KC-010197A150-60D-5000K-B-TDM