

MODEL : PM-05-24

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1: 240 mVp-p (Max)	I/P: 230VAC O/P:FULL LOAD Ta:25°C	V1: 59 mVp-p (Max)	P
2	OUTPUT VOLTAGE TOLERANCE	V1: 2 %~ -2 % (Max)	I/P:115 VAC / 264 VAC O/P:FULL/ MIN LOAD Ta:25°C	V1: 0.05 %~ -0.05 %	P
3	LINE REGULATION	V1: 0.5 %~ -0.5 % (Max)	I/P:115 VAC ~ 264 VAC O/P:FULL LOAD Ta:25°C	V1: 0.03 %~ -0.03 %	P
4	LOAD REGULATION	V1: 0.5 %~ -0.5 % (Max)	I/P: 230 VAC O/P:FULL ~MIN LOAD Ta:25°C	V1: 0.05 %~ -0.05 %	P
5	SET UP TIME	230VAC: 1000 ms (Max) 115 VAC: 1000 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 725 ms 115VAC/ 339 ms	P
6	RISE TIME	230VAC: 20 ms (Max) 115VAC: 20 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 10 ms 115VAC/ 10 ms	P
7	HOLD UP TIME	230VAC: 100 ms (TYP) 115VAC: 24 ms (TYP)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 160 ms 115VAC/ 37 ms	P
8	OVER/UNDERSHOOT TEST	< ±5%	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	TEST: <5 %	P
9	DYNAMIC LOAD	V1: 2400 mVp-p	I/P: 230 VAC O/P:FULL /Min LOAD 90%DUTY/1KHZ Ta:25°C	144 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	85VAC~264 VAC	I/P: TESTING O/P: FULL LOAD Ta: 25°C	46V~264V	P
			I/P: LOW-LINE-3V= 82 V HIGH-LINE+15%=300 V O/P: FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST: OK	
2	INPUT FREQUENCY RANGE	47HZ ~440 HZ NO DAMAGE OSC	I/P: 85 VAC ~ 264 VAC O/P: FULL~MIN LOAD Ta: 25°C	TEST: OK	P
3	EFFICIENCY	76 % (TYP)	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	76.9 %	P
4	INPUT CURRENT	230V/ 0.08 A (TYP) 115V/ 0.12 A (TYP)	I/P: 230 VAC I/P: 115 VAC O/P: FULL LOAD Ta: 25°C	I = 0.073 A/ 230 VAC I = 0.114 A/ 115 VAC	P
5	INRUSH CURRENT	230V/ 45 A (TYP) 115V/ 25 A (TYP) COLD START	I/P: 230 VAC I/P: 115 VAC O/P: FULL LOAD Ta: 25°C	I = 24 A/ 230 VAC I = 12 A/ 115 VAC	P
6	LEAKAGE CURRENT	<80uA /264 VAC for touch leakage current	I/P: 264 VAC O/P: Min LOAD Ta: 25°C	L-V+ : 69 uA L-V-: 69 uA N-V+: 69 uA N-V-: 69 uA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	Above 105 %	I/P: 230 VAC I/P: 115 VAC O/P: TESTING Ta: 25°C	157 %/ 230 VAC 149 %/ 115 VAC Hiccup Mode	P
2	OVER VOLTAGE PROTECTION	CH1: 27.6V~ 32.4V	O/P: MIN LOAD Ta: 25°C	30.4 V/ 100mA Shut off	P
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 264 VAC O/P: FULL LOAD Ta: 25°C	NO DAMAGE Hiccup Mode	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	No load power consumption	<0.5W	I/P: 240 VAC O/P: NO LOAD	0.44 W/ 240 VAC	P

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																																
1	TEMPERATURE RISE TEST	MODEL : PM-05-24 1. ROOM AMBIENT BURN-IN : 1.5 HRS I/P: 230VAC O/P: FULL LOAD Ta= 25 °C 2. HIGH AMBIENT BURN-IN : 2 HRS I/P: 230VAC O/P: FULL LOAD Ta= 50.8 °C <table><tr><th>NO</th><th>Position</th><th>P/N</th><th>ROOM AMBIENT Ta= 25 °C</th><th>HIGH AMBIENT Ta= 50.8°C</th></tr><tr><td>1</td><td>U1</td><td>DM0265RNB FAIR</td><td>52.6°C</td><td>76.2°C</td></tr><tr><td>2</td><td>D1</td><td>BYV26C 1A/600V VIS</td><td>48.2°C</td><td>71.3°C</td></tr><tr><td>3</td><td>ZD1</td><td>P6KE220A PAN</td><td>53.8°C</td><td>77.1°C</td></tr><tr><td>4</td><td>T1 COIL</td><td>TF-1391 LS</td><td>51.0°C</td><td>73.2°C</td></tr><tr><td>5</td><td>BD1</td><td>KBP208G 2A/800V LT</td><td>44.0°C</td><td>67.3°C</td></tr><tr><td>6</td><td>D100</td><td>HER203 2A/200V REC</td><td>46.0°C</td><td>68.4°C</td></tr><tr><td>7</td><td>C36</td><td>47U/50V RUB 105°C YXF</td><td>45.9°C</td><td>69.0°C</td></tr><tr><td>8</td><td>L100</td><td>DR006C</td><td>42.9°C</td><td>65.3°C</td></tr><tr><td>9</td><td>C105</td><td>100U/35V RUB 105°C YXF</td><td>43.3°C</td><td>65.7°C</td></tr><tr><td>10</td><td>C5</td><td>22U/400V RUB 105°C YXA</td><td>42.8°C</td><td>66.1°C</td></tr><tr><td>11</td><td>LF1</td><td>LF-502 LS</td><td>42.5°C</td><td>66.0°C</td></tr><tr><td>12</td><td></td><td></td><td></td><td></td></tr><tr><td>13</td><td></td><td></td><td></td><td></td></tr><tr><td>14</td><td></td><td></td><td></td><td></td></tr><tr><td>15</td><td></td><td></td><td></td><td></td></tr></table>			NO	Position	P/N	ROOM AMBIENT Ta= 25 °C	HIGH AMBIENT Ta= 50.8°C	1	U1	DM0265RNB FAIR	52.6°C	76.2°C	2	D1	BYV26C 1A/600V VIS	48.2°C	71.3°C	3	ZD1	P6KE220A PAN	53.8°C	77.1°C	4	T1 COIL	TF-1391 LS	51.0°C	73.2°C	5	BD1	KBP208G 2A/800V LT	44.0°C	67.3°C	6	D100	HER203 2A/200V REC	46.0°C	68.4°C	7	C36	47U/50V RUB 105°C YXF	45.9°C	69.0°C	8	L100	DR006C	42.9°C	65.3°C	9	C105	100U/35V RUB 105°C YXF	43.3°C	65.7°C	10	C5	22U/400V RUB 105°C YXA	42.8°C	66.1°C	11	LF1	LF-502 LS	42.5°C	66.0°C	12					13					14					15					P
NO	Position	P/N	ROOM AMBIENT Ta= 25 °C	HIGH AMBIENT Ta= 50.8°C																																																																																	
1	U1	DM0265RNB FAIR	52.6°C	76.2°C																																																																																	
2	D1	BYV26C 1A/600V VIS	48.2°C	71.3°C																																																																																	
3	ZD1	P6KE220A PAN	53.8°C	77.1°C																																																																																	
4	T1 COIL	TF-1391 LS	51.0°C	73.2°C																																																																																	
5	BD1	KBP208G 2A/800V LT	44.0°C	67.3°C																																																																																	
6	D100	HER203 2A/200V REC	46.0°C	68.4°C																																																																																	
7	C36	47U/50V RUB 105°C YXF	45.9°C	69.0°C																																																																																	
8	L100	DR006C	42.9°C	65.3°C																																																																																	
9	C105	100U/35V RUB 105°C YXF	43.3°C	65.7°C																																																																																	
10	C5	22U/400V RUB 105°C YXA	42.8°C	66.1°C																																																																																	
11	LF1	LF-502 LS	42.5°C	66.0°C																																																																																	
12																																																																																					
13																																																																																					
14																																																																																					
15																																																																																					
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P: 230 VAC O/P: 139 % LOAD Ta:25°C	TEST : OK	P																																																																																
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 230 VAC O/P: 100 % LOAD Ta= -20°C	TEST : OK	P																																																																																
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50°C NO DAMAGE	I/P: 272 VAC O/P:FULL LOAD Ta= 50°C HUMIDITY= 95 %R.H	TEST : OK	P																																																																																
5	TEMPERATURE COEFFICIENT	± 0.03 %(0~50°C)	I/P: 230 VAC O/P:FULL LOAD	± 0.01 %(0~50°C)	P																																																																																
6	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency:10~500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:2G (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25°C		TEST : OK	P																																																																																

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 4 KVAC/min	I/P-O/P: 4.4 KVAC/min Ta:25°C	I/P-O/P: 1.01 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P: 500 VDC Ta:25°C	I/P-O/P: 30 GΩ NO DAMAGE	P
3	APPROVAL	TUV: Certificate NO : TA50081369 UL: File NO :			P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	PASS	P
2	CONDUCTION	EN55022 EN55011 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL/50% LOAD Ta:25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 EN55011 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 MEDICAL AIR:8KV / Contact:6KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 MEDICAL INPUT: 2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 MEDICAL L-N :1KV L,N-PE:2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

M.T.B.F & LIFE CYCLE CALCULATION

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	CAPACITOR LIFE CYCLE	SUPPOSE C105 IS THE MOST CRITICAL COMPONENT I/P: 230VAC O/P:FULL LOAD Ta= 25°C LIFE TIME= 599760 HRS I/P: 230VAC O/P:FULL LOAD Ta= 50°C LIFE TIME= 134196 HRS			P
2	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 1513.4KHRS			P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	U1 Rated DM0265RNB : 660 V 1.5A	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2) Full Load (3)Output Short Ta:25℃	(1) 630 V (2) 620 V (3) 642 V	P
2	Diode Peak Voltage	D100 Rated HER204 : 300V 2A	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2) Full Load (3)Output Short Ta:25℃	(1) 155 V (2) 227 V (3) 283 V	P
3	Clamp Diode Peak Voltage	D1 Rated BYV26C : 600V 1 A	I/P:High-Line +3V = 267 V O/P: (1)Full Load (2) Dynamic Load 90%Duty/1KHz Ta:25℃	(1) 536 V (2) 536 V	P
4	Input Capacitor Voltage	C5 Rated :22u / 400V/ 105℃	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change (4)Burn in 1hour Ta:25℃	(1) 371 V (2) 375 V (3) 371 V (4) 371 V	P
5	Control IC Voltage Test	U1 Rated DM0265RNB : 20 V	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta:25℃	(1) 14.7 V (2) 10.7 V (3) 14.7 V	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2006/1/12	RD SAMPLE	PASS	VINCENT TSENG	MAX LIN
2006/4/7	PRODUCT SAMPLE W0602A12	PASS	VINCENT TSENG	MAX LIN

2003/12/12 A50-F023