



Test Report: PCD-25-1400B

25W Single Output AC Dimmable LED Power Supply

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1 : 2 Vp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 1.07 Vp-p (Max)	P
2	SET UP TIME	230VAC : 500 ms (Max)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 357.389 ms	P
3	OPERATING VOLTAGE RANGE	12V~18V	I/P : 230VAC O/P : CV MODE Ta : 25°C	O/P= 12V : 1.402 A O/P= 17V : 1.402 A	P
4	OVER/UNDERSHOOT TEST	< 25V	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : <25 V	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	180VAC~295 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C	154 V~295V	P
			I/P : LOW-LINE-3V= 177 V HIGH-LINE+15%=300 V O/P : FULL/MIN LOAD ON : 30 Sec . OFF : 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST : OK	
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P : 180 VAC ~ 295 VAC O/P : FULL~MIN LOAD Ta : 25°C	TEST : OK	P
3	POWER FACTOR	0.9 / 230 VAC(TYP) 0.9 / 277 VAC(TYP)	I/P : 230 VAC (FULL LOAD) I/P : 277 VAC (FULL LOAD) O/P : FULL LOAD Ta : 25°C	PF= 0.960 / 230 VAC PF= 0.91 / 277 VAC	P
4	EFFICIENCY	80 % (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	81.87 %	P
5	INPUT CURRENT	230V/ 0.3 A (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	I = 0.133 A/ 230 VAC	P
6	INRUSH CURRENT	230V/ 10 A (TYP) COLD START	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	I = 8 A/ 230 VAC	P
7	LEAKAGE CURRENT	< 0.5 mA / 240 VAC	I/P : 240 VAC O/P : Min LOAD Ta : 25°C	L-CASE : 0.01 mA N-CASE : 0.01 mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	95 % ~ 110 %	I/P : 230 VAC I/P : 180 VAC O/P : TESTING Ta : 25°C	100 %/ 230 VAC 100 %/ 180 VAC Constant Current Limiting recovers automatically after fault condition is removed.	P
2	OVER TEMPERATURE PROTECTION	SPEC : RTH1 : $95 \pm 10^{\circ}\text{C}$ O.T.P. Detect on heatsink of power transistor	I/P : 230 VAC O/P : FULL LOAD	O.T.P. Active Shut down o/p voltage , Re-power ON to recover	P
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 295 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE	P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q 1 Rated : STD4NK80ZT4 3A/800V	I/P : High-Line +3V = 298 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 600 V (2) 484 V (3) 568 V	P
2	Diode Peak Voltage	D100 Rated : VSSC520S 5A/200V	I/P : High-Line +3V = 298 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C	(1) 105 V (2) 86 V (3) 104 V	P
3	Clamp Diode Peak Voltage	D 6 Rated : 1A/1KV 1N4007GP	I/P : High-Line +3V = 298 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C	(1) 620 V (2) 480 V (3) 604 V	P
4	Control IC Voltage Test	U 1 Rated : PWM NCP1608B 10.2V~20V	I/P : High-Line +3V = 298 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 13.645 V (2) 12.078 V (3) 12.019 V	P

SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P : 3.75 KVAC/min	I/P-O/P : 4 KVAC/min Ta : 25°C	I/P-O/P : 1.161 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ	I/P-O/P : 500 VDC Ta : 25°C /70%RH	I/P-O/P : 30 GΩ NO DAMAGE	P
3	APPROVAL	TUV : Certificate NO : UL : File NO :			N/A

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS C	I/P:230 /240//220VAC/50HZ LOAD:LED/ELECTRONIC LOAD O/P:40V/58VLOAD Ta:25°C	PASS	P
2	CONDUCTION	EN55015 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL/50% LOAD Ta : 25°C	PASS Test by certified Lab	P
3	RADIATION	EN55015 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL LOAD Ta : 25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR : 8KV / Contact : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT : 1KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 LIGHT INDUSTRY L-N : 1KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																																															
1	TEMPERATURE RISE TEST	MODEL : PCD-25-1400B 1. ROOM AMBIENT BURN-IN : 1 HRS I/P : 230VAC O/P : FULL LOAD Ta=30.3℃ 2. HIGH AMBIENT BURN-IN : 3.5 HRS I/P : 230VAC O/P : FULL LOAD Ta= 50℃ <table><thead><tr><th>NO</th><th>Position</th><th>P/N</th><th>ROOM AMBIENT Ta= 30.3 ℃</th><th>HIGH AMBIENT Ta=50 ℃</th></tr></thead><tbody><tr><td>1</td><td>LF1</td><td>LF804</td><td>66.7℃</td><td>81.4℃</td></tr><tr><td>2</td><td>L1</td><td>TF2285</td><td>67.0℃</td><td>81.5℃</td></tr><tr><td>3</td><td>BD1</td><td>2A/800V GLASS KBP208G</td><td>70.1℃</td><td>84.4℃</td></tr><tr><td>4</td><td>C9</td><td>473/630V 10% P=7.5 MEX</td><td>65.2℃</td><td>79.5℃</td></tr><tr><td>5</td><td>R1</td><td>3W 22KΩ 5% MINI</td><td>92.6℃</td><td>109.5℃</td></tr><tr><td>6</td><td>R5</td><td>3W 1KΩ 5% MINI</td><td>75.0℃</td><td>91.4℃</td></tr><tr><td>7</td><td>C1</td><td>104/275VAC 20% P=10 R.46</td><td>74.7℃</td><td>89.2℃</td></tr><tr><td>8</td><td>D30</td><td>1A/1KV 1N4007GP</td><td>75.1℃</td><td>91.2℃</td></tr><tr><td>9</td><td>C48</td><td>22u/50V UL10Kh 5*11 YXM</td><td>75.4℃</td><td>89.8℃</td></tr><tr><td>10</td><td>TSW1</td><td>220KΩ 3Φ TTC3A224F4371EY 1%</td><td>72.2℃</td><td>88.1℃</td></tr><tr><td>11</td><td>T1</td><td>TF2154</td><td>87.4℃</td><td>100.1℃</td></tr><tr><td>12</td><td>U1</td><td>NCP1608B SOIC-8</td><td>74.5℃</td><td>88.7℃</td></tr><tr><td>13</td><td>Q1</td><td>STD4NK80ZT4 3A/800V DPAK</td><td>84.7℃</td><td>98.9℃</td></tr><tr><td>14</td><td>C7</td><td>473/630V 10% X7R 1812</td><td>70.8℃</td><td>85.9℃</td></tr><tr><td>15</td><td>D100</td><td>VSSC520S 5A/200V SMC</td><td>86.3℃</td><td>98.6℃</td></tr><tr><td>16</td><td>C105</td><td>1500u/25V UL10Kh 12.5*20 ZLH</td><td>69.0℃</td><td>82.5℃</td></tr><tr><td>17</td><td>C54</td><td>33u/50V UL10Kh 6.3*11 YXM</td><td>74.2℃</td><td>88.3℃</td></tr><tr><td>18</td><td>LF100</td><td>LF804</td><td>62.7℃</td><td>76.3℃</td></tr></tbody></table>			NO	Position	P/N	ROOM AMBIENT Ta= 30.3 ℃	HIGH AMBIENT Ta=50 ℃	1	LF1	LF804	66.7℃	81.4℃	2	L1	TF2285	67.0℃	81.5℃	3	BD1	2A/800V GLASS KBP208G	70.1℃	84.4℃	4	C9	473/630V 10% P=7.5 MEX	65.2℃	79.5℃	5	R1	3W 22KΩ 5% MINI	92.6℃	109.5℃	6	R5	3W 1KΩ 5% MINI	75.0℃	91.4℃	7	C1	104/275VAC 20% P=10 R.46	74.7℃	89.2℃	8	D30	1A/1KV 1N4007GP	75.1℃	91.2℃	9	C48	22u/50V UL10Kh 5*11 YXM	75.4℃	89.8℃	10	TSW1	220KΩ 3Φ TTC3A224F4371EY 1%	72.2℃	88.1℃	11	T1	TF2154	87.4℃	100.1℃	12	U1	NCP1608B SOIC-8	74.5℃	88.7℃	13	Q1	STD4NK80ZT4 3A/800V DPAK	84.7℃	98.9℃	14	C7	473/630V 10% X7R 1812	70.8℃	85.9℃	15	D100	VSSC520S 5A/200V SMC	86.3℃	98.6℃	16	C105	1500u/25V UL10Kh 12.5*20 ZLH	69.0℃	82.5℃	17	C54	33u/50V UL10Kh 6.3*11 YXM	74.2℃	88.3℃	18	LF100	LF804	62.7℃	76.3℃	P
NO	Position	P/N	ROOM AMBIENT Ta= 30.3 ℃	HIGH AMBIENT Ta=50 ℃																																																																																																
1	LF1	LF804	66.7℃	81.4℃																																																																																																
2	L1	TF2285	67.0℃	81.5℃																																																																																																
3	BD1	2A/800V GLASS KBP208G	70.1℃	84.4℃																																																																																																
4	C9	473/630V 10% P=7.5 MEX	65.2℃	79.5℃																																																																																																
5	R1	3W 22KΩ 5% MINI	92.6℃	109.5℃																																																																																																
6	R5	3W 1KΩ 5% MINI	75.0℃	91.4℃																																																																																																
7	C1	104/275VAC 20% P=10 R.46	74.7℃	89.2℃																																																																																																
8	D30	1A/1KV 1N4007GP	75.1℃	91.2℃																																																																																																
9	C48	22u/50V UL10Kh 5*11 YXM	75.4℃	89.8℃																																																																																																
10	TSW1	220KΩ 3Φ TTC3A224F4371EY 1%	72.2℃	88.1℃																																																																																																
11	T1	TF2154	87.4℃	100.1℃																																																																																																
12	U1	NCP1608B SOIC-8	74.5℃	88.7℃																																																																																																
13	Q1	STD4NK80ZT4 3A/800V DPAK	84.7℃	98.9℃																																																																																																
14	C7	473/630V 10% X7R 1812	70.8℃	85.9℃																																																																																																
15	D100	VSSC520S 5A/200V SMC	86.3℃	98.6℃																																																																																																
16	C105	1500u/25V UL10Kh 12.5*20 ZLH	69.0℃	82.5℃																																																																																																
17	C54	33u/50V UL10Kh 6.3*11 YXM	74.2℃	88.3℃																																																																																																
18	LF100	LF804	62.7℃	76.3℃																																																																																																
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 230VAC/100VAC O/P : 100 % LOAD Ta= -30 ℃	TEST : OK	P																																																																																															
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 40 ℃ NO DAMAGE	I/P : 295 VAC O/P : FULL LOAD Ta= 40 ℃ HUMIDITY= 95 %R.H	TEST : OK	P																																																																																															
4	TEMPERATURE COEFFICIENT	± 0.03 %(0~40℃)	I/P : 230 VAC O/P : FULL LOAD	± 0.003 %(0~40℃)	P																																																																																															
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45℃~ +90℃ 2. Temperature change rate : 25℃ / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK	P																																																																																															

6	THERMAL SHOCK TEST	1. Thermal shock Temperature : -30℃~ +40℃ 2. Temperature change rate : 25℃ / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec	OK	P
7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 2G (5) Test Time : 72min in each axis (X.Y.Z) (6) Ta : 25℃	TEST : OK	P
8	CAPACITOR LIFE CYCLE	PCD-25-1400B:SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta=25 °C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta=50 °C LIFE TIME	(1) 213797 HRS (2) 58119 HRS	P
9	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE : 906.5 HRS		P
10	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure(Expected Life) : 30,000 hours @ Tcase 75℃ ; 50,000 hours @ Tcase 65℃		P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2010/10/6	RD SAMPLE	PASS	SANFORD SU	VINCENT TSENG
2010/11/10	PRODUCT SAMPLE	PASS	SANFORD SU	VINCENT TSENG

2009/08/04 A50-F023